

Ktwo
sales



Eco Muck Spreader

Models - 50-8, 60-9, 75-11



Eco Muck Spreaders

Standard Equipment:

- Fully welded construction
- Dynamically balanced twin vertical beaters
- Reversible boron beater teeth
- High tensile 50mm diameter floor drive shafts
- Cross line relief valve floor protection
- Full width socket on floor slats
- Variable floor speed control
- Grade 80 floor chains
- 6 tooth floor drive sprockets
- Wide angle front PTO shaft
- Shearbolt driveline protection
- One piece Rogelberg rotor gearbox
- 540rpm PTO input speed
- Grease banking to top rotor bearings
- Full LED road lights with automatic covers
- Single pole drawbar

Optional Equipment:

- Slurry door
- Wooden greedy boards
- Larger wheel equipment

Model	50-8	60-9	75-11
Design capacity (kg)	5,000	6,000	7,500
Volume - Level filled (m ³)	4.2	4.9	6.3
Volume - Level 225mm ext. (m ³)	5.6	6.5	8.2
Volume - Max. heaped (m ³)	7.8	9.0	10.8
Axle beam (mm)	80 x 80	80 x 80	80 x 80
No. of axle studs / Brake size (mm)	8 / 355 x 80	8 / 355 x 80	8 / 355 x 80
Standard wheels	16.9 x 30 14PR	16.9 x 30 14PR	18.4 x 34 14PR
No. of floor chains & chain size (mm)	2 x 14	2 x 14	2 x 14
Rear floor drive roller diameter (mm)	50	50	50
PTO Input speed (rpm)	540	540	540
Power requirement (hp)	75	85	95
Dimensions: (mm/feet)			
A) Overall length	5,380 / 17'7"	5,880 / 19'3"	6,330 / 20'9"
B) Overall height	2,350 / 7'8"	2,350 / 7'8"	2,530 / 8'3"
C) Loading height	1,750 / 5'9"	1,750 / 5'9"	1,930 / 6'4"
D) Rear overhang	1,490 / 4'11"	1,605 / 5'3"	1,745 / 5'9"
L) Internal length	3,380 / 11'1"	3,880 / 12'9"	4,330 / 14'3"
H) Internal height	800 / 2'8"	800 / 2'8"	900 / 2'11"
Overall width	2,560 / 8'5"	2,560 / 8'5"	2,600 / 8'6"
Loading width	1,850 / 6'1"	1,850 / 6'1"	1,950 / 6'5"
Internal width	1,500 / 4'11"	1,500 / 4'11"	1,500 / 4'11"



K Two Sales Ltd, Fowlers Field Farm, Station Road, Haddenham, Aylesbury, Buckinghamshire, HP17 8DD

Tel: +44(0)1844 299 290 Fax: +44(0)1844 299 390 Email: paul@ktwosales.co.uk

www.ktwosales.co.uk