

CURVE

Rodeo Curve Trailer

KEY FEATURES

- High quality and heavy-duty trailer.
- Mono tipping cylinders give a fast and efficient tip with rapid return/drop.
- High tensile steel used in body panels for increased strength and lower nett weight.
- LED lighting equipment for maximum visibility including tailgate repeater lights and LED flashing beacon.
- Fully commercial running gear c/w 10 stud axles with 420 x 180mm brakes for maximum braking efficiency.
- Drawbar box section 200 x 200 x 12mm.
- 48T parabolic spring set for stability, ride performance and minimal maintenance whilst providing the best of on and off-road handling characteristics.
- A sprung drawbar and tridem sprung axles come as standard to ensure a stable and comfortable ride.
- Bolt on GKN hitch giving options of fixed, swivel and K80 spoon.
- Front arched viewing window on all models.
- Hydraulic tailgate fitted with a hydraulic safety valve with mechanical 6 point locking.
- Shot blasted paint preparation, finished with two pack paint.
- Mudguards, mud flaps, light guards and access ladder all as standard.



ROADEO CURVE Trailer

SPECIFICATIONS

	MODEL
	2800 TRI AXLE
Design capacity	28,000 kg / 61,729 lb
Volume – Grain	29 m ³ / 1,024 cu ft
Volume – Silage	52 m ³ / 1,850 cu ft
Axle track width (mm)	2,200
Axle beam (mm)	120 x 120
Brake size (mm)	420 x 180
Axle springs – no. of leaves / leaf size (mm)	3 / 100 x 26
Tipping cylinders x capacity (l)	187 x 6 / 51
Floor thickness (mm)	5
Side thickness (mm)	4
Sprung drawbar	Std.
Front arch window	Std.
Fixed hitch	Std.
Standard wheels	800 / 45 R26.5



DIMENSIONS

	mm	ft
Overall length	9,520	31'3"
Overall height - grain	2,840	9'4"
Overall height - silage	3,840	12'7"
Internal body length	7,700	25'3"
Internal height - grain	1,330	4'4"
Tipped height - grain	8,080	26'6"
Tipped height - silage	8,640	28'4"
Average internal width	2,900	9'6"
Maximum external width	3,200	10'6"

